

Secure Seal[®] LDCS/LDCD

Single-Wall, Double-Wall 26" to 36" diameter.
Special Gas Vent. Listed to UL 1738 and ULC S636.

Applications

- Category I, II, III and IV gas-fired appliances
- Type BH gas vent systems for appliances having a maximum flue temperature of 480°F.
- May also be used for high-efficiency gas boilers, furnaces, booster heaters, pool heaters, water heaters, unit heaters or tankless water heaters.
- No need to apply silicone on-site at section joint; each joint seals with our Viton[®] O-ring system, a non-silicone construction designed to withstand the corrosive nature of the condensate.

Materials and Construction

Inner Wall: 26" to 36" AL29-4C[®] (0.035")
Outer Wall: 26" to 36", 441 (0.024")

Diameters

26"-36"

Listings

Tested and listed to UL 1738 and ULC S636.

Warranty

15 Years



Secure Seal[®] LDCS/LDCD

Secure Seal[®] LDCS/LDCD

Single-Wall, Double-Wall 26" to 36" diameter.

Special Gas Vent. Listed to UL 1738 and ULC S636.

Features	Benefits
Laser butt-welding	<ul style="list-style-type: none">• Reinforces strength• Prevents leakage• Increases durability and reliability
Secure Seal viton sealing gaskets	<ul style="list-style-type: none">• Self-sealing - no need to apply sealing material when pieces are joined together• Easier and faster installation
Standard adjustable vent length	<ul style="list-style-type: none">• Provides vertical or horizontal adjustment for easy system pitching
AL29-4C stainless steel	<ul style="list-style-type: none">• Resists the extreme corrosive environments found in condensing boilers• Assures safe and trouble-free operation
Proven track record	<ul style="list-style-type: none">• Conformed to UL1738 and certified to ULC-S636• 15-year warranty
All accessories made of stainless steel	<ul style="list-style-type: none">• For durability



Secure Seal[®] LDCS/LDCD

